

17" (16.0" VIS) Real Flat monitor

- 17-inch (16.0" VIS) Real Flat colour monitor with excellent front of screen performance for use with MACs and PCs
- Autoscan covers horizontal frequencies up to 71 kHz offering a maximum resolution of 1280 x 1024 with flicker free display of 1024 x 768 at up to 89 Hz
- Real Flat High Contrast CRT with high-resolution 0.25 mm dot pitch (0.21 hdp)
- XSD-Xtra Space Design for large screen display in a small footprint: World's shortest 17-inch Real Flat monitor with maximum depth of only 419 mm/16.5"
- Multimedia Base and USB Hub option



Optional Multimedia base 6G3B11

Optional USB HUB PCUH411

Let's make things better.



PHILIPS

17" (16.0" VIS) Real Flat monitor



Technical Specifications

CRT

- Size (inch/cm) 17"/ 41 cm
- Deflection angle (degrees) 90°
- Dot pitch 0.25 mm
- Horizontal pitch 0.21 mm
- Tube type Shadow mask, Real Flat, High Contrast, Anti Glare, Anti Static, Anti reflection, Light Transmission 45%
- Phosphor P22
- Recom. display area(mm) 306 x 230 mm
- Recom. display area(inch) 12.0" x 9.0"
- Max. display area(mm) 325 x 244 mm
- Max. display area(inch) 12.8" x 9.6"

Scanning

- Horizontal scanning 30 - 71 kHz
- Vertical scanning 50 - 160 Hz

Video

- Video dot rate 108 MHz
- Input impedance -Video 75 Ohm
- Sync 2.2k Ohm
- Input signal levels 0.7 Vpp
- Sync input signal Separate sync
- Composite sync
- Sync polarities Positive and negative

White colour temperature

Chromaticity CIE coordinates:

- at 9300 K: x=0.283, y=0.297
- at 6500 K: x=0.313, y=0.329

Resolution and preset modes

- Max. resolution 1280 x 1024
 - Recom. resolution 1024 x 768
 - 16 user definable modes
 - 22 factory preset modes:
- | | H.freq (kHz)/V.freq (Hz) |
|-------------|--------------------------|
| 640 x 350 | 31.5K/70 |
| 640 x 350 | 37.9K/85 |
| 640 x 480 | 31.5K/60 |
| 640 x 480 | 37.9K/72 |
| 640 x 480 | 37.5K/75 |
| 640 x 480 | 43.3K/85 |
| 640 x 480 | 50.6K/100 |
| 720 x 400 | 31.5K/70 |
| 720 x 400 | 37.9K/85 |
| 800 x 600 | 37.9K/60 |
| 800 x 600 | 48.1K/72 |
| 800 x 600 | 46.9K/75 |
| 800 x 600 | 53.7K/85 |
| 800 x 600 | 63.9K/100 |
| 832 x 624 | 49.7K/75 |
| 1024 x 768 | 48.4K/60 |
| 1024 x 768 | 56.5K/70 |
| 1024 x 768 | 60.0K/75 |
| 1024 x 768 | 68.7K/85 |
| 1152 x 864 | 67.5K/75 |
| 1280 x 960 | 60.0K/60 |
| 1280 x 1024 | 64.0K/60 |

Plug and play compatibility

- Display Data Channel DDC 2B (VESA)
- Microsoft® Windows® 95/98/Me & 2000/NT/XP compatible
- sRGB

Power management

Complies with EPA Energy Star and NUTEK specifications

- Operation 68 W (typical)
- Suspend/Stand By mode < 2 W
- Off mode/Deep Sleep < 2 W

Low-emission characteristics

- Complies with MPR-II

Monitor controls and functions

- Main 5-button OSD
Brightness +/- direct access
Contrast +/- direct access
- On Screen Display Language (English, Spanish, French, German, Italian, Chinese, Portuguese, Korean), zoom, horizontal, vertical, pincushion, balanced, trapezoid, parallelogram, colour, reset, degauss, moire, serial number, resolution, frequency, sRGB

Connections and Cables

- Connections -Video 15-pin D-sub
- Cables D-Sub Video cable(fixed), power cord

Regulatory approvals

- MPR-II Low Emission
- TÜV/GS, TÜV/Ergo, TÜV/9241-3
- FCC-B, UL, CSA, DHHS
- SEMKO, Poland-B sign, C-Tick
- CE, BCIQ, PSB
- NUTEK, Energy Star

Physical specifications

- Dim. incl. base (WxHxD)(mm) 399 x 410 x 419
- Dim. incl. base (WxHxD)(inch) 15.7" x 16.1" x 16.5"
- Dim. excl. base (WxHxD)(mm) 399 x 373 x 419
- Dim. excl. base (WxHxD)(inch) 15.7" x 14.7" x 16.5"
- Weight (kg) 16.5 kg
- Power supply 90 - 264 VAC, 50/60Hz
- Temperature (operational) 0°C to 40°C/ 32°F to 104° F
- Temperature (storage) -25°C to 65°C/ -13°F to 149°F
- Relative humidity 5% to 95%
- MTBF > 75,000 H

Other

- USB Hub option type: PCUH411
- Multimedia Base option type: 6G3B11

As an Energy Star partner, Philips has determined that this product meets the Energy Star guidelines for energy efficiency.
Microsoft and Windows are registered trademarks of Microsoft Corporation
MacOS is a registered trademark of Apple Computer, Inc.
All trademark acknowledged. Copyright 2001 Koninklijke Philips Electronics N.V.

All data subject to change without notice

Release date: May 2002

www.philips.com

Let's make things better.



PHILIPS